

**Description**

Fastener Length: 2-1/4", Hole Diameter: 5/64", Thread: 1/4-28, Thread Length: 2-1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS56471                                  |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-01-205-9125                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS564-71 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 2.132 Inches Minimum And 2.250 Inches Maximum  |
| <b>Fastener Length:</b>                               | 2.203 Inches Minimum And 2.250 Inches Maximum  |
| <b>Head Style:</b>                                    | Hexagon  |
| <b>Head Height:</b>                                   | 0.209 Inches Minimum And 0.229 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.428 Inches Minimum And 0.440 Inches Maximum  |
| <b>Hole Diameter:</b>                                 | 0.070 Inches Minimum And 0.080 Inches Maximum  |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Hole Quantity:</b>                                 | 3  |
| <b>Hole Type:</b>                                     | Drilled  |
| <b>Features Provided:</b>                             | Finished Head  |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  |
| <b>Hole Configuration Style:</b>                      | Hexagon Corners  |
| <b>Surface Finish:</b>                                | 63.0 Microinches Bearing Surface Of Head   |
| <b>Surface Finish:</b>                                | 63.0 Microinches Threads   |
| <b>Material:</b>                                      | Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas564 Professional/industrial Association Standard  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS564-71> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.