

Description

Fastener Length: 2-7/16", Hole Diameter: 5/64", Thread: 1/4-28, Thread Length: 2-13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS56477
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-422-8677
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS564-77 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.330 Inches Minimum And 2.407 Inches Maximum
Fastener Length:	2.390 Inches Minimum And 2.437 Inches Maximum
Head Style:	Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Corners
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas564 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS564-77> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.