

**Description**

Fastener Length: 1-11/16", Hole Diameter: 5/64", Thread: 1/4-28, Thread Length: 1-11/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS564C53                                 |
| Minimum Qty (MOQ):      | 2   |
| NSN:                    | 5306-01-099-0926                          |
| Schedule B:             | 7318.15.2091                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS564C53 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 1.569 Inches Minimum And 1.687 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 1.640 Inches Minimum And 1.687 Inches Maximum                       |
| <b>Head Style:</b>                                    | Hexagon   |
| <b>Head Height:</b>                                   | 0.209 Inches Minimum And 0.229 Inches Maximum                       |
| <b>Width Between Flats:</b>                           | 0.428 Inches Minimum And 0.440 Inches Maximum                       |
| <b>Hole Diameter:</b>                                 | 0.070 Inches Minimum And 0.080 Inches Maximum                       |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches  |
| <b>Hole Quantity:</b>                                 | 3   |
| <b>Hole Type:</b>                                     | Drilled   |
| <b>Features Provided:</b>                             | Finished Head   |
| <b>Thread Quantity Per Inch:</b>                      | 28  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| <b>Hole Configuration Style:</b>                      | Hexagon Corners   |
| <b>Material:</b>                                      | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b>          | Ams5731 Assn Std Single Material Response Overall                   |
| <b>Surface Treatment:</b>                             | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall                  |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas564 Professional/industrial Association Standard           |

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS564C53> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.