



Military-Fasteners.com

P/N NAS564C55

Description

Fastener Length: 1-3/4", Hole Diameter: 5/64", Thread: 1/4-28, Thread Length: 1-23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS564C55
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-133-0138
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS564C55 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.643 Inches Minimum And 1.720 Inches Maximum
Fastener Length:	1.703 Inches Minimum And 1.750 Inches Maximum
Head Style:	Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Hole Quantity:	3
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Corners
Part Name Assigned By Controlling Agency:	Navy Special Project
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas564 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS564C55> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.