

# P/N NAS565-25

Military-Fasteners.com

#### Description

Fastener Length: 3/4", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 3/4"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS56525
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-531-1849
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS565-25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.721 Inches Minimum And 0.751 Inches Maximum
Fastener Length:	0.781 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.500 Inches Nominal
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.030 Inches Minimum And 0.060 Inches Maximum
Hole Quantity:	6
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Longitudinal Hole
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

### How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/NAS565-25</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.