

**Description**

Fastener Length: 15/16", Thread: 1/4-24, Thread Length: 29/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS56531                                  |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5306-00-816-2729                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS565-31 Specifications

|                                  |   |
|----------------------------------|---|
| <b>Thread Class:</b>             | 3a  |
| <b>Thread Direction:</b>         | Right-hand  |
| <b>Thread Length:</b>            | 0.908 Inches Minimum  |
| <b>Fastener Length:</b>          | 0.968 Inches Nominal  |
| <b>Head Style:</b>               | Hexagon   |
| <b>Head Height:</b>              | 0.281 Inches Nominal  |
| <b>Width Between Flats:</b>      | 0.578 Inches Nominal  |
| <b>Nominal Thread Diameter:</b>  | 0.312 Inches  |
| <b>Grip Length:</b>              | 0.060 Inches Nominal  |
| <b>Features Provided:</b>        | Finished Head   |
| <b>Thread Quantity Per Inch:</b> | 24  |
| <b>Minimum Tensile Strength:</b> | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>          | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| <b>Material:</b>                 | Steel Overall   |
| <b>Surface Treatment:</b>        | Cadmium Overall   |
| <b>Thread Series Designator:</b> | Unf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS565-31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.