

Description

Fastener Length: 15/16", Thread: 1/4-24, Thread Length: 29/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS56531
Minimum Qty (MOQ):	10 EA
NSN:	5306-00-816-2729
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS565-31 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.908 Inches Minimum
Fastener Length:	0.968 Inches Nominal
Head Style:	Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.578 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.060 Inches Nominal
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS565-31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.