

Description

Fastener Length: 1-1/16", Thread: 1/4-24, Thread Length: 1", NAS565 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS56533
Minimum Qty (MOQ):	5
NSN:	5306-00-967-9576
Schedule B:	7318.15.2095
ECCN:	EAR99
National Motor Freight:	093470, Bolts / Nuts I / S



* See page 2 for technical characteristics

P/N NAS565-33 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.000 Inches Minimum
Fastener Length:	1.015 Inches Minimum And 1.062 Inches Maximum
Head Style:	Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas565 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS565-33> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.