Military-Fasteners.com

P/N NAS565-57

Description

Fastener Length: 1-13/16", Hole Diameter: 5/64", Thread: 1/4-24, Thread Length: 1-13/16", NAS565 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS56557
Minimum Qty (MOQ):	5
NSN:	5306-01-170-6129
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)




* See page 2 for technical characteristics

P/N NAS565-57 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.682 Inches Minimum And 1.812 Inches Maximum
Fastener Length:	1.765 Inches Minimum And 1.812 Inches Maximum
Head Style:	Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Hole Quantity:	3
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Corners
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas565 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS565-57 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.