

## **P/N NAS565C31**

### **Description**

Fastener Length: 31/32", Thread Length: 33/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS565C31

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-551-4303



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS565C31 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.519 Inches Nominal
Fastener Length:	0.969 Inches Nominal
Head Style:	Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.500 Inches Nominal
Thread Quantity Per Inch:	24
Part Name Assigned By Controlling Agency:	Bolt-full Threaded,160 Ksi Steel,drilled Head
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

# **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS565C31">https://military-fasteners.com/bolts/machine+bolts/NAS565C31</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS565C31">https://military-fasteners.com/bolts/machine+bolts/NAS565C31</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS565C31">https://military-fasteners.com/bolts/machine+bolts/NAS565C31</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/machine+bolts/NAS565C31">https://military-fasteners.com/bolts/machine+bolts/NAS565C31</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/nas6565C31">https://military-fasteners.com/bolts/nas6565C31</a> and selecting the property of the property