

Description

Fastener Length: 1-13/16", Hole Diameter: 5/64", Thread: 1/4-24, Thread Length: 1-3/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS565C37
Minimum Qty (MOQ):	5
NSN:	5306-01-304-2708
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS565C37 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.721 Inches Minimum And 1.751 Inches Maximum
Fastener Length:	1.765 Inches Minimum And 1.812 Inches Maximum
Head Style:	Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Hole Quantity:	3
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Corners
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas565 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS565C37> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.