

Description

Fastener Length: 1-25/32", Hole Diameter: 5/64", Thread: 1/4-24, Thread Length: 1-3/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information**Alternate Part Numbers**[NAS565-C57](#)

| | |
|-------------------------|---|
| SKU / Model: | NAS565C57 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-113-9078 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS565C57 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.711 Inches Minimum And 1.761 Inches Maximum |
| Fastener Length: | 1.771 Inches Minimum And 1.791 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.281 Inches Nominal |
| Width Between Flats: | 0.490 Inches Minimum And 0.502 Inches Maximum |
| Hole Diameter: | 0.070 Inches Minimum And 0.080 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Hole Quantity: | 3 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Corners |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas 565 Professional/industrial Association Standard |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS565C57> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.