

P/N NAS566-27

Description

Fastener Length: 27/32", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 13/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| SKU / Model: | NAS56627 |
|-------------------------|---|
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5306-00-841-1818 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



^{*} See page 2 for technical characteristics

P/N NAS566-27 Specifications

| Thread Class: | 3a |
|--|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.784 Inches Minimum And 0.814 Inches Maximum |
| Fastener Length: | 0.844 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.281 Inches Nominal |
| Width Between Flats: | 0.562 Inches Nominal |
| Hole Diameter: | 0.070 Inches Nominal |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 0.030 Inches Minimum And 0.060 Inches Maximum |
| Hole Quantity: | 6 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Longitudinal Hole |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall |
| Material Document And Classification: | Mil-b-6812 Mil Spec All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS566-27 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS566-27 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS566-27 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/NAS566-27 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/nas64 and selecting the property of the pr