

## **P/N NAS566-47**

### **Description**

Fastener Length: 1-1/2", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 1-15/32"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS56647
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-448-6198
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS566-47 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.393 Inches Minimum And 1.470 Inches Maximum
Fastener Length:	1.453 Inches Minimum And 1.500 Inches Maximum
Head Style:	Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.552 Inches Minimum And 0.564 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.375 Inches
Hole Quantity:	6
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Longitudinal Hole
Material:	Steel Comp 4140 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6758 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas566 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/NAS566-47">https://military-fasteners.com/bolts/machine+bolts/NAS566-47</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.