



Military-Fasteners.com

P/N NAS566C121

Description

Fastener Length: 3-13/16", Hole Diameter: 5/64", Thread: 3/8-24, Thread Length: 3-25/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS566C121
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-172-5536
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS566C121 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	3.705 Inches Minimum And 3.782 Inches Maximum
<b>Fastener Length:</b>	3.765 Inches Minimum And 3.812 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.281 Inches Nominal
<b>Width Between Flats:</b>	0.552 Inches Minimum And 0.564 Inches Maximum
<b>Hole Diameter:</b>	0.070 Inches Minimum And 0.080 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Hole Quantity:</b>	3
<b>Hole Type:</b>	Drilled
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Hole Configuration Style:</b>	Hexagon Corners
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas566 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS566C121> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.