

Description

Fastener Length: 2-1/4", Hole Diameter: 5/64", Thread: 3/8-24, Thread Length: 1-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS566C71
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-285-2014
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS566C71 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.016 Inches Minimum And 2.220 Inches Maximum
Fastener Length:	2.159 Inches Minimum And 2.250 Inches Maximum
Head Style:	Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.552 Inches Minimum And 0.564 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
First Diameter From Head:	0.3450 Inches Minimum And 0.3750 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.030 Inches Minimum And 0.060 Inches Maximum
Point Style:	Flat
Nominal Thread Diameter:	0.375 Inches
Hole Quantity:	6
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Externally Relieved Body Diameter Quantity:	1
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas566 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS566C71> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.