

**Description**

Fastener Length: 1-5/8", Hole Diameter: 5/64", Thread: 1/2-20, Thread Length: 1-37/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS568C53
Minimum Qty (MOQ):	1
NSN:	5306-01-589-4873
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS568C53 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.580 Inches Nominal
<b>Fastener Length:</b>	1.656 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.375 Inches Nominal
<b>Width Between Flats:</b>	0.740 Inches Minimum And 0.752 Inches Maximum
<b>Hole Diameter:</b>	0.070 Inches Minimum And 0.080 Inches Maximum
<b>Grip Diameter:</b>	0.464 Inches Minimum And 0.500 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Grip Length:</b>	0.030 Inches Minimum And 0.060 Inches Maximum
<b>Hole Quantity:</b>	3
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS568C53> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.