

Description

Fastener Length: 1-5/8", Hole Diameter: 5/64", Thread: 1/2-20, Thread Length: 1-37/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS568C53
Minimum Qty (MOQ):	1
NSN:	5306-01-589-4873
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS568C53 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.580 Inches Nominal
Fastener Length:	1.656 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.375 Inches Nominal
Width Between Flats:	0.740 Inches Minimum And 0.752 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Grip Diameter:	0.464 Inches Minimum And 0.500 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	0.030 Inches Minimum And 0.060 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS568C53> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.