

Description

Fastener Length: 3/8", Thread: 4-40, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS57006
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-132-3356
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS5700-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.256 Inches Minimum And 0.336 Inches Maximum
Fastener Length:	0.350 Inches Minimum And 0.380 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.193 Inches Minimum And 0.226 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas5700 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5700-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.