

**Description**

Fastener Length: 3/8", Thread: 6-32, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS5701U6
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-183-3317
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS5701U6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.380 Inches Nominal
<b>Fastener Length:</b>	0.380 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.246 Inches Minimum And 0.280 Inches Maximum
<b>Internal Drive Style:</b>	Tri-wing Recess
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas5701 Professional/industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5701U6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.