



Military-Fasteners.com

P/N NAS5703U9

Description

Fastener Length: 35/64", Thread: 10-32, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS5703U9
Minimum Qty (MOQ):	25 EA
NSN:	5305-01-260-9340
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS5703U9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.478 Inches Nominal
Fastener Length:	0.530 Inches Minimum And 0.560 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response Or Ams5737 Assn Std Single Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Nas4003 Assn Std Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas5703 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5703U9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.