

Description

Fastener Length: 11/16", Thread: 1/4-28, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS5704U11 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-183-7897 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS5704U11 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.690 Inches Nominal |
| Fastener Length: | 0.690 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.456 Inches Minimum And 0.508 Inches Maximum |
| Internal Drive Style: | Tri-wing Recess |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas5704 Professional/industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5704U11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.