

Description

Fastener Length: 7/8", Thread: 1/4-28, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS5704U14
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-183-7899
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS5704U14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.880 Inches Nominal
Fastener Length:	0.880 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.456 Inches Minimum And 0.508 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams 5731 Assn Std Single Material Response Or Ams 5737 Assn Std Single Material Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas5704 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5704U14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.