

Description

NAS574-2 Headless Shoulder Pin

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS5742
Minimum Qty (MOQ):	10
NSN:	5315-00-614-3589
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS574-2 Specifications

First End Style:	Chamfered
Second End Style:	Round
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.339 Inches Nominal
Shank Length:	0.364 Inches Minimum And 0.384 Inches Maximum
Shoulder Width Across Flats:	0.240 Inches Minimum And 0.260 Inches Maximum
Shank Diameter:	0.190 Inches Nominal
Overall Length:	1.000 Inches Minimum And 1.060 Inches Maximum
First End Taper Length:	0.047 Inches Nominal
Second End Relationship With First End:	Not Identical
Nominal Thread Size:	0.190 Inches
Second Shank Diameter:	0.210 Inches Minimum And 0.215 Inches Maximum
First End Location:	Long End
First End Taper Angle:	45.0 Degrees Nominal
Second End Outer Radius:	0.063 Inches Nominal
Second Shank Length:	0.521 Inches Minimum And 0.541 Inches Maximum
Material:	Steel Comp 303 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Style Designator:	Shoulder
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas574 Professional/industrial Association Standard

How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/NAS574-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.