

**Description**

NAS574-2 Headless Shoulder Pin

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS5742
Minimum Qty (MOQ):	10
NSN:	5315-00-614-3589
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9

NO IMAGE  
AVAILABLE

## P/N NAS574-2 Specifications

<b>First End Style:</b>	Chamfered
<b>Second End Style:</b>	Round
<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.339 Inches Nominal
<b>Shank Length:</b>	0.364 Inches Minimum And 0.384 Inches Maximum
<b>Shoulder Width Across Flats:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Shank Diameter:</b>	0.190 Inches Nominal
<b>Overall Length:</b>	1.000 Inches Minimum And 1.060 Inches Maximum
<b>First End Taper Length:</b>	0.047 Inches Nominal
<b>Second End Relationship With First End:</b>	Not Identical
<b>Nominal Thread Size:</b>	0.190 Inches
<b>Second Shank Diameter:</b>	0.210 Inches Minimum And 0.215 Inches Maximum
<b>First End Location:</b>	Long End
<b>First End Taper Angle:</b>	45.0 Degrees Nominal
<b>Second End Outer Radius:</b>	0.063 Inches Nominal
<b>Second Shank Length:</b>	0.521 Inches Minimum And 0.541 Inches Maximum
<b>Material:</b>	Steel Comp 303 Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-s-5002 Mil Spec Single Treatment Response Overall
<b>Style Designator:</b>	Shoulder
<b>Thread Series Designator:</b>	Unc
<b>Specification/standard Data:</b>	80205-nas574 Professional/industrial Association Standard

## How to Order

Order this straight headless pin from our inventory online by visiting <https://military-fasteners.com/pins/straight+headless+pins/NAS574-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.