

## **P/N NAS574-2**

### **Description**

NAS574-2 Headless Shoulder Pin

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS5742

Minimum Qty (MOQ): 10

NSN: 5315-00-614-3589

ECCN: EAR99

National Motor Freight: 095190, Hardware, Noi Sub 9



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS574-2 Specifications**

First End Style:	Chamfered
Second End Style:	Round
Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.339 Inches Nominal
Shank Length:	0.364 Inches Minimum And 0.384 Inches Maximum
Shoulder Width Across Flats:	0.240 Inches Minimum And 0.260 Inches Maximum
Shank Diameter:	0.190 Inches Nominal
Overall Length:	1.000 Inches Minimum And 1.060 Inches Maximum
First End Taper Length:	0.047 Inches Nominal
Second End Relationship With First End:	Not Identical
Nominal Thread Size:	0.190 Inches
Second Shank Diameter:	0.210 Inches Minimum And 0.215 Inches Maximum
First End Location:	Long End
First End Taper Angle:	45.0 Degrees Nominal
Second End Outer Radius:	0.063 Inches Nominal
Second Shank Length:	0.521 Inches Minimum And 0.541 Inches Maximum
Material:	Steel Comp 303 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Overall
Style Designator:	Shoulder
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas574 Professional/industrial Association Standard

## **How to Order**

Order this straight headless pin from our inventory online by visiting <a href="https://military-fasteners.com/pins/straight+headless+pins/NAS574-2">https://military-fasteners.com/pins/straight+headless+pins/NAS574-2</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.