

Description

Thread Size: 1-1/4", Nut Height: 1-13/16", Nut Length: 2-11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS577B20A
Minimum Qty (MOQ):	1 EA
NSN:	5310-01-210-3874
Schedule B:	7318.16.0085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS577B20A Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Nut Style:	Floating Self-locking Barrel
Nut Diameter:	2.119 Inches Minimum And 2.122 Inches Maximum
Nut Length:	2.342 Inches Minimum And 2.362 Inches Maximum
Barrel Height:	1.310 Inches Minimum And 1.320 Inches Maximum
Nut Height:	1.813 Inches Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	12
Hardness Rating:	39.0 Rockwell C Minimum And 46.0 Rockwell C Maximum
Nominal Thread Size:	1.250 Inches
Material:	Steel Comp 8740 Or Steel Comp 4340 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Or Ms 6322 Fed Spec Single Material Response Or Mil-s-8844,cl 1 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas577 Professional/industrial Association Standard

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS577B20A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.