

Description

Thread Size: 1-1/4", Nut Height: 1-13/16", Nut Length: 2-11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS577B20A |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5310-01-210-3874 |
| Schedule B: | 7318.16.0085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS577B20A Specifications

| | |
|---|--|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Dry Film Lubricant |
| Nut Style: | Floating Self-locking Barrel |
| Nut Diameter: | 2.119 Inches Minimum And 2.122 Inches Maximum |
| Nut Length: | 2.342 Inches Minimum And 2.362 Inches Maximum |
| Barrel Height: | 1.310 Inches Minimum And 1.320 Inches Maximum |
| Nut Height: | 1.813 Inches Maximum |
| Thread Series: | Unjf |
| Features Provided: | Floating Nut |
| Thread Quantity Per Inch: | 12 |
| Hardness Rating: | 39.0 Rockwell C Minimum And 46.0 Rockwell C Maximum |
| Nominal Thread Size: | 1.250 Inches |
| Material: | Steel Comp 8740 Or Steel Comp 4340 Overall |
| Material Document And Classification: | Mil-s-6049 Mil Spec 1st Material Response Or Ms 6322 Fed Spec Single Material Response Or Mil-s-8844,cl 1 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Cadmium And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Specification/standard Data: | 80205-nas577 Professional/industrial Association Standard |

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS577B20A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.