

Description

thread: 1/4-28, NAS577 series nut

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS577B4A
Minimum Qty (MOQ):	2
NSN:	5310-01-232-3542
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS577B4A Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Nut Style:	Floating Self-locking Barrel
Nut Diameter:	0.525 Inches Minimum And 0.528 Inches Maximum
Nut Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Barrel Height:	0.310 Inches Minimum And 0.320 Inches Maximum
Nut Height:	0.406 Inches Maximum
Temp Rating:	Not Rated
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	28
Hardness Rating:	Not Rated
Nominal Thread Size:	0.250 Inches
Material:	Steel Comp 8740 Or Steel Comp 4340 Overall
Material Document And Classification:	Ams 6322 Assn Std 1st Material Response Or Mil-s-6049 Mil Spec 1st Material Response Or Mil-s-8844 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas577 Professional/industrial Association Standard

How to Order

Order this self-locking barrel nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+barrel+nuts/NAS577B4A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.