

P/N NAS577B5A

Description

thread: 5/16-24, floating

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS577B-5A

SKU / Model: NAS577B5A

Minimum Qty (MOQ): 2

NSN: 5310-00-839-2017

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS577B5A Specifications

| 3b |
|---|
| Right-hand |
| Prevailing Torque All Metal Design |
| 0.344 Inches Minimum Nut And 0.354 Inches Maximum Nut |
| Dry Film Lubricant |
| Floating Self-locking Barrel |
| 0.587 Inches Minimum And 0.590 Inches Maximum |
| 0.678 Inches Minimum And 0.698 Inches Maximum |
| 0.350 Inches Minimum And 0.360 Inches Maximum |
| 0.468 Inches Minimum |
| 0.120 Inches Minimum Nut And 0.130 Inches Maximum Nut |
| 450.0 Deg Fahrenheit Nominal |
| Unjf |
| Floating Nut |
| 24 |
| 36.0 Rockwell C Minimum And 43.0 Rockwell C Maximum |
| 0.312 Inches |
| Steel Comp 4140 Nut Or Steel Comp 8740 Nut Or Steel Comp E4340 Nut |
| Mil-s-5626 Mil Spec 1st Material Response Nut Or Mil-s-6049 Mil Spec 2nd Material Response Nut Or Mil-s-5000 Mil Spec 3rd Material Response Nut |
| Cadmium Overall |
| Qq-p-416 Fed Spec Single Treatment Response Overall |
| 80205-nas577 Professional/industrial Association Standard |
| |

How to Order

Order this self-locking barrel nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+barrel+nuts/NAS577B5A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.