

Description

Thread Size: 3/8", Nut Length: 5/8", Nut Height: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS577B5F
Minimum Qty (MOQ):	1 EA
NSN:	5310-01-251-2922
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS577B5F Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Nut Style:	Floating Self-locking Barrel
Nut Diameter:	0.587 Inches Minimum And 0.590 Inches Maximum
Nut Length:	0.678 Inches Minimum And 0.688 Inches Maximum
Barrel Height:	0.350 Inches Minimum And 0.360 Inches Maximum
Nut Height:	0.468 Inches Maximum
Thread Series:	Unjf
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.3125 Inches
Special Features:	Dry Film Lubricant
Material:	Steel Comp 8740 Overall Or Steel Comp 4340 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Mil-s-8844,class 1 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas 672 Assn Std 1st Treatment Response Overall Or Mil-c-8837 Mil Spec 2nd Treatment Response Overall
Specification/standard Data:	80205-nas577 Professional/industrial Association Standard

How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS577B5F> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.