

**Description**

Thread Size: 3/8", Nut Length: 5/8", Nut Height: 1/2"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS577B5F
Minimum Qty (MOQ):	1 EA
NSN:	5310-01-251-2922
Schedule B:	7318.16.0085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS577B5F Specifications

<b>Thread Class:</b>	3b
<b>Thread Direction:</b>	Right-hand
<b>Locking Feature:</b>	Prevailing Torque All Metal Design
<b>Lubrication:</b>	Dry Film Lubricant
<b>Nut Style:</b>	Floating Self-locking Barrel
<b>Nut Diameter:</b>	0.587 Inches Minimum And 0.590 Inches Maximum
<b>Nut Length:</b>	0.678 Inches Minimum And 0.688 Inches Maximum
<b>Barrel Height:</b>	0.350 Inches Minimum And 0.360 Inches Maximum
<b>Nut Height:</b>	0.468 Inches Maximum
<b>Thread Series:</b>	Unjf
<b>Thread Quantity Per Inch:</b>	24
<b>Nominal Thread Size:</b>	0.3125 Inches
<b>Special Features:</b>	Dry Film Lubricant
<b>Material:</b>	Steel Comp 8740 Overall Or Steel Comp 4340 Overall
<b>Material Document And Classification:</b>	Mil-s-6049 Mil Spec 1st Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Mil-s-8844,class 1 Mil Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Nas 672 Assn Std 1st Treatment Response Overall Or Mil-c-8837 Mil Spec 2nd Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas577 Professional/industrial Association Standard

## How to Order

Order this locknut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS577B5F> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.