

Description

Thread: 3/8-24, floating

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS577B6A
Minimum Qty (MOQ):	2
NSN:	5310-01-255-6579
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS577B6A Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Nut Style:	Floating Self-locking Barrel
Nut Diameter:	0.681 Inches Minimum And 0.684 Inches Maximum
Nut Length:	0.740 Inches Minimum And 0.760 Inches Maximum
Barrel Height:	0.410 Inches Minimum And 0.420 Inches Maximum
Nut Height:	0.531 Inches Maximum
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.375 Inches
Material:	Steel Comp 8740 Overall Or Steel Comp 4340 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Ams 6322 Assn Std 1st Material Response Overall Or Mil-s-8844,cl 1 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas577 Professional/industrial Association Standard

How to Order

Order this self-locking barrel nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+barrel+nuts/NAS577B6A and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.