

**Description**

Thread Size: 27/64", Nut Length: 7/8", Nut Height: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS577B7A                                 |
| Minimum Qty (MOQ):      | 1   |
| NSN:                    | 5310-01-317-8989                          |
| Schedule B:             | 7318.16.0085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS577B7A Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3b  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Locking Feature:</b>                               | Prevailing Torque All Metal Design  |
| <b>Lubrication:</b>                                   | Dry Film Lubricant  |
| <b>Nut Style:</b>                                     | Floating Self-locking Barrel  |
| <b>Nut Diameter:</b>                                  | 0.775 Inches Minimum And 0.778 Inches Maximum   |
| <b>Nut Length:</b>                                    | 0.865 Inches Minimum And 0.875 Inches Maximum   |
| <b>Barrel Height:</b>                                 | 0.460 Inches Minimum And 0.470 Inches Maximum   |
| <b>Nut Height:</b>                                    | 0.625 Inches Maximum  |
| <b>End Item Identification:</b>                       | C-5b Aircraft   |
| <b>Thread Series:</b>                                 | Unjf  |
| <b>Thread Quantity Per Inch:</b>                      | 20  |
| <b>Nominal Thread Size:</b>                           | 0.437 Inches  |
| <b>Material:</b>                                      | Steel Comp 8740 Overall Or Steel Comp 4340 Overall  |
| <b>Material Document And Classification:</b>          | Mil-s-6049 Mil Spec 1st Material Response Overall Or Ams 6322 Assn Std 1st Material Response Overall Or Mil-s-8844,class 1 Mil Spec 2nd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall   |
| <b>Specification/standard Data:</b>                   | 80205-nas577 Professional/industrial Association Standard   |

## How to Order

Order this plain hexagon nut from our inventory online by visiting <https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS577B7A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.