

## **P/N NAS577B8F**

## **Description**

Thread Size: 1/2", Nut Length: 1", Nut Height: 45/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS577B8F

Minimum Qty (MOQ): 1 EA

NSN: 5310-01-219-5954

Schedule B: 7318.16.0085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS577B8F Specifications**

Thread Class:	3b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque All Metal Design
Lubrication:	Dry Film Lubricant
Nut Style:	Floating Self-locking Barrel
Nut Diameter:	0.869 Inches Minimum And 0.872 Inches Maximum
Nut Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Barrel Height:	0.530 Inches Minimum And 0.540 Inches Maximum
Nut Height:	0.703 Inches Maximum
End Item Identification:	C-5b Aircraft
Temp Rating:	Not Rated
Thread Series:	Unjf
Features Provided:	Floating Nut
Thread Quantity Per Inch:	20
Hardness Rating:	Not Rated
Nominal Thread Size:	0.500 Inches
Material:	Steel Comp 8740 Or Steel Comp 4340 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Or Ams 6322 Assn Std 1st Material Response Or Mil-s-8844 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Nas672 Assn Std Single Treatment Response Or Mil-c-8837 Mil Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas577 Professional/industrial Association Standard

### **How to Order**

Order this cap plate - two lug locknut from our inventory online by visiting <a href="https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS577B8F">https://military-fasteners.com/nuts/plain+hexagon+nuts/NAS577B8F</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.