

Description

Fastener Length: 19/64", Thread: 8-32, Thread Length: 3/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS5802U5
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-184-5138
Schedule B:	8108.90.3060
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS5802U5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.199 Inches Nominal
Fastener Length:	0.280 Inches Minimum And 0.310 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.296 Inches Minimum And 0.331 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Titanium Alloy
Screw Material Document And Classification:	Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas5802 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5802U5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.