

Description

Fastener Length: 1-1/4", Thread: 10-32, Thread Length: 1-5/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS5803U20 |
| Minimum Qty (MOQ): | 30 EA |
| NSN: | 5305-01-185-6271 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N NAS5803U20 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.168 Inches Nominal |
| Fastener Length: | 1.190 Inches Minimum And 1.250 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.338 Inches Minimum And 0.381 Inches Maximum |
| Internal Drive Style: | Tri-wing Recess |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Titanium Alloy |
| Screw Material Document And Classification: | Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas5803 Professional/industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5803U20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.