

Description

Fastener Length: 1-39/64", Thread: 10-32, Thread Length: 1-17/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS5803U26
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-185-6273
Schedule B:	8108.90.3060
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N NAS5803U26 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.538 Inches Nominal
<b>Fastener Length:</b>	1.560 Inches Minimum And 1.620 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.338 Inches Minimum And 0.381 Inches Maximum
<b>Internal Drive Style:</b>	Tri-wing Recess
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Titanium Alloy
<b>Screw Material Document And Classification:</b>	Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas5803 Professional/industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5803U26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.