

Description

Fastener Length: 1-39/64", Thread: 10-32, Thread Length: 1-17/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS5803U26
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-185-6273
Schedule B:	8108.90.3060
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS5803U26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.538 Inches Nominal
Fastener Length:	1.560 Inches Minimum And 1.620 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Minimum And 0.381 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Titanium Alloy
Screw Material Document And Classification:	Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas5803 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5803U26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.