

P/N NAS583-2

Description

Fastener Length: 17/32", Thread: 10-32, Thread Length: 27/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS5832
Minimum Qty (MOQ):	5
NSN:	5305-00-514-7499
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS583-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.381 Inches Minimum And 0.431 Inches Maximum
Fastener Length:	0.516 Inches Minimum And 0.546 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.339 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas583 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS583-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/close+tolerance+screws/NAS583-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/close+tolerance+screws/NAS583-2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners.com/screws/nase-">https://military-fasteners