

P/N NAS583-20

Description

Fastener Length: 1-11/16", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS58320

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-816-1193

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS583-20 Specifications

Thread Direction: Right-hand Thread Length: 0.406 Inches Minimum And 1.687 Inches Maximum Thread Length: 1.640 Inches Minimum And 1.687 Inches Maximum Thread Style: Flat Countersunk Thread Diameter: 0.376 Inches Minimum And 0.381 Inches Maximum Thread Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Thread Diameter: 0.190 Inches Thread Diameter: 0.190 Inches Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Thread Quantity Per Inch: 32 Thread Quantity Per Inch: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Thread Diameter: 99.0 Degrees Minimum And 101.0 Degrees Maximum Thread Diameter: 32.0 Microinches Grip Thread Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Thread Countersink Angle: Steel Comp 4130 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Thread Countersink Angle: Steel Comp 4130 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Thread Length: 1.640 Inches Minimum And 1.687 Inches Maximum Lead Style: Flat Countersunk Lead Diameter: 0.376 Inches Minimum And 0.381 Inches Maximum Lead Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Lead Diameter: 0.190 Inches Minimum And 0.1895 Inches Maximum Lead Diameter: 0.190 Inches Minimum And 0.1895 Inches Maximum Lead Diameter: 0.190 Inches Lead Diameter: 0.190 Inches Lead Diameter: 0.190 Inches Lead Quantity Per Inch: Lead Q
Flat Countersunk Head Style: Flat Countersunk Head Diameter: 0.376 Inches Minimum And 0.381 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: High-torque Johninal Thread Diameter: 0.190 Inches 1.250 Inches Nominal Thread Quantity Per Inch: 1.250 Inches Nominal Thread Quantity Per Inch: High-torque Johninum Tensile Strength: 1.60000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Jountersink Angle: Jountersink Angle: 32.0 Microinches Grip 33.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Flat Countersunk O.376 Inches Minimum And 0.381 Inches Maximum O.1885 Inches Minimum And 0.1895 Inches Maximum O.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: High-torque Jominal Thread Diameter: 0.190 Inches Internal Drive Style: 1.250 Inches Nominal Internal Quantity Per Inch: 32 Internal Quantity Per Inch: 32 Internal Grip Length: 160000 Pounds Per Square Inch Internal Grip Length: 160000 Pounds Per Square Inch Internal Quantity Per Inch: 32 Internal Grip Length: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Internal Grip Length: 32.0 Microinches Grip Internal Grip Length: 32.0 Microinches Threads
Head Diameter: 0.376 Inches Minimum And 0.381 Inches Maximum 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: High-torque Idominal Thread Diameter: 0.190 Inches Incread Quantity Per Inch: 32 Idinimum Tensile Strength: 160000 Pounds Per Square Inch Idardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Iduntation Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Idurface Finish: 32.0 Microinches Grip Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Idurface Increase Incr
Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: High-torque Idominal Thread Diameter: 0.190 Inches Grip Length: 1.250 Inches Nominal Thread Quantity Per Inch: 32 Idinimum Tensile Strength: 160000 Pounds Per Square Inch Idardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Idurface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Anterial:
High-torque Jominal Thread Diameter: Journal
Addresial: 0.190 Inches 0.190
1.250 Inches Nominal Thread Quantity Per Inch: Alimimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Anterial:
Chread Quantity Per Inch: Alinimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Grip 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Angle: 10000 Pounds Per Square Inch 10000 Pounds
Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall
32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or St
Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Stee
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Over
Naterial:
of Steel Comp 4150 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall
Surface Treatment: Cadmium Overall And Chromate Overall
Gurface Treatment Document And Classification: Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unf
Specification/standard Data: 80205-nas583 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS583-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/close+tolerance+screws/NAS583-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/close+tolerance+screws/NAS583-20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/nas683-20 and selecting the quantity you want https://military-fasteners.com/screws/nas683-20 and selecting the property of the property o