

P/N NAS583-23

Description

Fastener Length: 1-7/8", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS58323

Minimum Qty (MOQ): 10 EA

NSN: 5305-00-804-1986

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS583-23 Specifications

Thread Direction: Right-hand Thread Length: 0.406 Inches Minimum Asstener Length: 1.828 Inches Minimum And 1.875 Inches Maximum Idead Style: Flat Countersunk Idead Style: Flat Countersunk Idead Diameter: 0.376 Inches Minimum And 0.381 Inches Maximum Idead Diameter: 0.385 Inches Minimum And 0.381 Inches Maximum Internal Drive Style: High-torque Idead Diameter: 0.190 Inches Idead Diameter: 0	Thread Class:	3a
Abea Length: 0.406 Inches Minimum Instener Length: 1.828 Inches Minimum And 1.875 Inches Maximum Island Style: Flat Countersunk Island Dlameter: 0.376 Inches Minimum And 0.381 Inches Maximum Isrip Diameter: 0.1885 Inches Minimum And 0.389 Inches Maximum Isrip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Isrip Diameter: 0.190 Inches Minimum And 0.1895 Inches Maximum Isrip Diameter: 0.190 Inches Minimum And 0.1895 Inches Maximum Isrip Diameter: 0.190 Inches Minimum And 0.1895 Inches Maximum Isrip Diameter: 0.190 Inches Minimum Thread Diameter: 0.190 Inches Isrip Length: 1.438 Inches Nominal Isrip Length: 1.438 Inches Maximum And 10.1.0 Degrees Maximum Overall Or Secondary Noverall Or Steel Comp Popular Inches		
lead Style: Flat Countersunk lead Diameter: 0.376 Inches Minimum And 0.381 Inches Maximum orito Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum nternal Drive Style: High-torque lominal Thread Diameter: 0.190 Inches orito Length: 1.438 Inches Nominal thread Quantity Per Inch: 32 dinimum Tensile Strength: 160000 Pounds Per Square Inch lardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum surface Finish: 32.0 Microinches Grip surface Finish: 32.0 Microinches Grip diaterial: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall alaterial Document And classification: Mili-s-5626 Mil Spec 1st Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Mili-s-6758 mil Spec 6th Material Response Overall org-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall org-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall		
lead Style: Flat Countersunk		
lead Diameter: 0.376 Inches Minimum And 0.381 Inches Maximum internal Drive Style: High-torque Itominal Thread Diameter: 0.190 Inches Irip Length: 1.438 Inches Nominal Irhread Quantity Per Inch: 32 Itinimum Tensile Strength: 160000 Pounds Per Square Inch Idinimum Tensile Strength: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Idinimum Tensile Strength: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Idinimum Tensile Strength: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Idinimum Tensile Strength: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Idinimum Tensile Strength: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Idinimum Tensile Strength: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Idinimum Tensile Strength: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Idinimum Tensile Strength: 36.0 Rockwell C Minimum Overall And 10.0 Degrees Maximum Idinimum Tensile Strength: 36.0 Rockwell C Minimum Overall And 10.0 Rockwell C Maximum Overall Idinimum Tensile Strength: 36.0 Rockwell C Minimum Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Idinimum Tensile Strength: 36.0 Rockwell C Minimum Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Idinimum Tensile Strength: 36.0 Rockwell C Minimum Overall Or Mili-s-6098 Mil Spec 2nd Material Response Overall Or Mili-s-6049 Mil Spec 5th Material Response Overall Or Mili-s-6049 Mili Spec 5th Material Response Overall Or Mili	Fastener Length:	1.828 Inches Minimum And 1.875 Inches Maximum
Internal Drive Style: High-torque Internal Drive Style: High-torque Internal Drive Style: 1.438 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: High-torque Indiniant Thread Diameter: 0.190 Inches Internal Drive Style: 1.438 Inches Nominal Internal Quantity Per Inch: 32 Intimum Tensile Strength: 160000 Pounds Per Square Inch Internal Drive Style: 160000 Pounds Per Square Inch Internal Strength: 160000 Pounds Per Square Inch Internal Drive Style: 160000 Pounds Per Square Inch Internal Drive Internal Pounds International Pounds International Pounds International Pounds International Pounds International Pou	Head Style:	Flat Countersunk
High-torque High-torque Jominal Thread Diameter: Jung Length: Jung L	Head Diameter:	0.376 Inches Minimum And 0.381 Inches Maximum
Journal Thread Diameter: 1.438 Inches Nominal 1.438 Inches Nomin	Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Infection 1.438 Inches Nominal Infection 2. Infection 2. Infinitum Tensile Strength: 160000 Pounds Per Square Inch Information Tensile Strength: 160000 Pounds Per Square Inch Information Pounds Per Square Inch I	Internal Drive Style:	High-torque
Infraed Quantity Per Inch: Infraed Quantity Per Inch: Info@000 Pounds Per Square Inch Info@000 Pounds Inch Info@000 Pou	Nominal Thread Diameter:	0.190 Inches
Alarenial Document And Classification: 160000 Pounds Per Square Inch 160000 Pounds Per S	Grip Length:	1.438 Inches Nominal
lardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Grip 32.0 Microinches Threads 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall 36.0 Rockwell C Maximum Overall Or Steel Comp 8740 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overa	Thread Quantity Per Inch:	32
99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Grip 32.0 Microinches Threads 32	Minimum Tensile Strength:	160000 Pounds Per Square Inch
32.0 Microinches Grip 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Gradmium Overall And Chromate Overall Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Gurface Treatment Cadmium Overall And Chromate Overall Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Cadmium Overall And Chromate Overall Oq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Surface Finish:	32.0 Microinches Grip
Or Steel Comp 4130 Overall Material Document And Classification: Or Steel Comp 4130 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Cadmium Overall And Chromate Overall Oq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Surface Finish:	32.0 Microinches Threads
Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Cadmium Overall And Chromate Overall Gurface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Material:	
Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Material Document And Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758
Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
hread Series Designator: Unit	Thread Series Designator:	Unf
pecification/standard Data: 80205-nas583 Professional/industrial Association Standard	Specification/standard Data:	80205-nas583 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS583-23 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/close+tolerance+screws/NAS583-23 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/close+tolerance+screws/NAS583-23 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/nas683-23 and selecting the quantity you want https://military-fasteners.com/screws/nas683-23 and selecting the property of the property o