

P/N NAS583-25

Description

Fastener Length: 1-63/64", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS58325

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-889-2922

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS583-25 Specifications

Thread Direction: Right-hand Thread Length: 0.406 Inches Minimum Fastener Length: 1.952 Inches Minimum And 1.999 Inches Maximum Head Style: Flat Countersunk Head Style: Flat Countersunk Head Diameter: 0.376 Inches Minimum And 0.381 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.190 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Mili-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or-9-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Thread Series Designator: Unf	Thursd Class	
Thread Length: 0.406 Inches Minimum Fastener Length: 1.952 Inches Minimum And 1.999 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.376 Inches Minimum And 0.381 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.190 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Material: 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Mill-s-6626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Surface Treatment: Cadmium Overall And Chromate Overall Ord-streatment Document And Classification: Unf	Thread Class:	
Fastener Length: Head Style: Head Style: Head Diameter: 0.376 Inches Minimum And 0.381 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.190 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec Gth Material Response Overall Orep-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Thread Series Designator: Unf		Right-hand
Head Style: Flat Countersunk Head Diameter: 0.376 Inches Minimum And 0.381 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.190 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Countersink Angle: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Mil-s-6026 Mil Spec 1st Material Response Overall Or Mil-s-6409 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Ord Freatment: Cadmium Overall And Chromate Overall Ord-16.152 C.1 3 Fed Spec All Treatment Responses Overall Ord-16.153 Fed Spec All Treatment Responses Overall	Thread Length:	0.406 Inches Minimum
Head Diameter: 0.376 Inches Minimum And 0.381 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.190 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-6026 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Material Document And Classification: Cadmium Overall And Chromate Overall Surface Treatment: Cadmium Overall And Chromate Overall Material Document And Classification: Cadmium Overall And Chromate Overall Material Document Pocument And Classification: Cadmium Overall And Chromate Overall Material Document Pocument Pocument And Classification: Cadmium Overall And Chromate Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Material Document Pocument Pocum	Fastener Length:	1.952 Inches Minimum And 1.999 Inches Maximum
Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.190 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unf	Head Style:	Flat Countersunk
Internal Drive Style: High-torque Nominal Thread Diameter: 0.190 Inches Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4150 Overall Or Steel Comp 8740 Overall Or Steel Comp 4150 Overall Or Steel Comp 8740 Overall Or Steel Comp 4150 Overall Or Steel Comp 8740 Overall Or Steel Comp 4150 Overall Or Mil-s-6038 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 6th Material Response Overall Or Mil-s-6058 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec Material Response Overall Or Mil-s-6058 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec Material Response Overall Or Mil-s-6058 Mil Spec Material Response Overall Or Mil-s-6049 Mil Spec Material Response Overall Or Mil-s-6058 Mil Spec Material Response Overall Or Mil-s-6049 Mil Spec Mater	Head Diameter:	0.376 Inches Minimum And 0.381 Inches Maximum
Nominal Thread Diameter: Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6	Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Grip Length: 1.562 Inches Nominal Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Material: Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Gree Treatment: Cadmium Overall And Chromate Overall Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Thread Series Designator: Unf	Internal Drive Style:	High-torque
Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Surface Treatment Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unf	Nominal Thread Diameter:	0.190 Inches
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Threads Streac Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Material: Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Thread Series Designator: Unf	Grip Length:	1.562 Inches Nominal
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Grip 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Material: Steel Comp 4130 Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Thread Series Designator: Unf	Thread Quantity Per Inch:	32
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Grip 32.0 Microinches Threads Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overa	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Thread Series Designator: Unf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Unf Unf	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Mil-s-6026 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil Spec 5th Material Respo	Surface Finish:	32.0 Microinches Grip
Material: Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unf	Surface Finish:	32.0 Microinches Threads
Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unf	Material:	
Surface Treatment Document And Classification: Thread Series Designator: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Unf	Material Document And Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758
And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Thread Series Designator: Unf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Specification/standard Data: 80205-nas583 Professional/industrial Association Standard	Thread Series Designator:	Unf
	Specification/standard Data:	80205-nas583 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS583-25 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/close+tolerance+screws/NAS583-25 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/close+tolerance+screws/NAS583-25 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/nas683-25 and selecting the quantity you want https://military-fasteners.com/screws/nas683-25 and selecting the property of the property o