

P/N NAS583-7

Military-Fasteners.com

#### Description

Fastener Length: 55/64", Thread: 10-32, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

### **Additional Information**

SKU / Model:	NAS5837
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-639-7249
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS583-7 Specifications

За
Right-hand
0.406 Inches Minimum
0.829 Inches Minimum And 0.859 Inches Maximum
Flat Countersunk
0.339 Inches Minimum And 0.381 Inches Maximum
0.1885 Inches Minimum And 0.1895 Inches Maximum
High-torque
0.190 Inches
0.438 Inches Nominal
32
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
100.0 Degrees Nominal
32.0 Microinches Grip
32.0 Microinches Threads
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas583 Professional/industrial Association Standard

# How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/close+tolerance+screws/NAS583-7</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.