

## P/N NAS584-44

## **Description**

Fastener Length: 3-1/4", Thread: 1/4-28, Thread Length: 15/32"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS58444

Minimum Qty (MOQ): 1 EA

NSN: 5305-00-905-3089

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS584-44 Specifications**

Thread Class: 3a  Thread Direction: Right-hand  Thread Length: 0.469 Inches Minimum  Fastener Length: 3.203 Inches Minimum And 3.250 Inches Maximum  Head Style: Flat Countersunk  Head Diameter: 0.502 Inches Minimum And 0.507 Inches Maximum	
Thread Length: 0.469 Inches Minimum  Fastener Length: 3.203 Inches Minimum And 3.250 Inches Maximum  Head Style: Flat Countersunk	
Fastener Length: 3.203 Inches Minimum And 3.250 Inches Maximum  Head Style: Flat Countersunk	
Head Style: Flat Countersunk	
<b>Head Diameter:</b> 0.502 Inches Minimum And 0.507 Inches Maximum	
<b>Grip Diameter:</b> 0.2485 Inches Minimum And 0.2495 Inches Maximum	
Internal Drive Style: High-torque	
Nominal Thread Diameter: 0.250 Inches	
Grip Length: 2.750 Inches Nominal	
Thread Quantity Per Inch: 28	
Minimum Tensile Strength: 160000 Pounds Per Square Inch	
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall	
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum	
Surface Finish: 32.0 Microinches Grip	
Surface Finish: 32.0 Microinches Threads	
Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp Or Steel Comp 4130 Overall	p 8740 Overall
Material Document And Classification:  Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-	
Surface Treatment: Cadmium Overall And Chromate Overall	
Surface Treatment Document And Classification:  Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	
Thread Series Designator: Unjf	
Specification/standard Data: 80205-nas584 Professional/industrial Association Standard	

### **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS584-44">https://military-fasteners.com/screws/close+tolerance+screws/NAS584-44</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS584-44">https://military-fasteners.com/screws/close+tolerance+screws/NAS584-44</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/nas64">https://military-fasteners.com/screws/close+tolerance+screws/NAS584-44</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/nas64">https://military-fasteners.com/screws/nas64</a> and selecting the quantity you want <a href="https://military-fasteners.com/screws/nas64">https://military-fasteners.com/screws/nas64</a> and selecting the quantity you want <a href="https://military-fasteners.com/screws/nas64">https://military-fasteners.com/screws/nas64</a> and selecting the quantity you want <a href="https://military-fasteners.com/screws/nas64">https://military-fasteners.com/screws/nas64</a> and selecting the property of the prop