

P/N NAS584-7

Description

Military-Fasteners.com

Fastener Length: 15/16", Thread: 1/4-28, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS5847
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-527-4424
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS584-7 Specifications

Tread Direction:Bight-handThread Length:0.469 Inches Minimum And 0.937 Inches MaximumFastener Length:0.890 Inches Minimum And 0.937 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.502 Inches Minimum And 0.2495 Inches MaximumOrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:High-torqueNominal Thread Diameter:0.250 Inches0.250 InchesMinimum And 0.2495 Inches MaximumThread Quantity Per Inche:0.250 InchesGrip Langth:0.438 Inches NominalThread Quantity Per Inche:28Minimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum And 10.10 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4130 OverallOr Steel Comp 4130 Overall Or Steel Comp E340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8730 Overall Or Steel Comp 4130 OverallMaterial:Cardinium Coverall And Chromate Overall Or Mil-s-5004 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 3th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Respo	Thursday Classes	
Thread Length:0.469 Inches Minimum And 0.937 Inches MaximumFastener Length:0.890 Inches Minimum And 0.937 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.502 Inches Minimum And 0.2495 Inches MaximumO.502 Inches Minimum And 0.2495 Inches Maximum10.507 Inches MaximumInternal Drive Style:High-torqueNominal Thread Diameter:0.250 Inches MaximumOrigi Diameter:0.438 Inches NominalOrigi Diameter:0.438 Inches NominalOrigi Diameter:0.438 Inches NominalOrigi Length:0.438 Inches NominalMinimum Tensile Strength:160000 Pounds Per Square InchMinimum Tensile Strength:160000 Pounds Per Square InchSurface Finish:30.0 Rockwell C Minimum And 10.10 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Steel Comp 4130 Overall Or Steel Comp E4340 Overall Or Steel Comp B150 Overall Or Steel Comp B730 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallMateriat Tereatment:Cardimi Overall And Chromate OverallMateriat Tereatment:Cardimi Overall	Thread Class:	За
Fastener Length:0.890 Inches Minimum And 0.937 Inches MaximumHead Style:Flat CountersunkHead Diameter:0.502 Inches Minimum And 0.507 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:High-torqueNominal Thread Diameter:0.250 Inches0.250 Inches Minimum And 0.2495 Inches MaximumGrip Length:0.438 Inches NominalThread Quantity Per Inch:28Biono Pounds Per Square InchHardnes Rating:0.6000 Pounds Per Square InchHardnes Rating:0.90 Degrees Minimum And 0.10 Degrees Maximum OverallCountersink Angle:9.0.0 Degrees Minimum And 10.10 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Sin Counters ThreadsRaterial:Sin Counters ThreadsSurface Finish:32.0 Microinches GripSurface Teatment AndGapy-Disteil Comp Ed340 O	Thread Direction:	Right-hand
Head Style:Flat CountersunkHead Diameter:0.502 Inches Minimum And 0.507 Inches MaximumGrip Diameter:0.502 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:High-torqueNominal Thread Diameter:0.250 InchesO Jaß Inches Nominal0.308 Inches NominalThread Quantity Per Inch:28Biotop Double Style:160000 Pounds Per Square InchHardness Rating:0.50.0 Rockwell C Maximum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:9.00 Degrees Minimum And 10.10 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Teatment And Classification:Steel Comp 4140 Overall Or Steel Comp E1340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Mil-s-6508 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 505 Milseps 30 Milseps 37 MilsepsSurface Treatment And Classification:Gonp-416, V2, cl 3 Fed Spec Single Treatment Response OverallSurface Treatment DocumeGrip Overall And Chromate OverallSurface Treatment DocumeGonp-416, V2, cl 3 Fed Spec Single Treatment Response Overal	Thread Length:	0.469 Inches Minimum
Head Diameter:0.502 Inches Minimum And 0.507 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:High-torqueNominal Thread Diameter:0.250 Inches0.500 Inches0.438 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Mil-5-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6503 Mil Spec 3rd MaterialSurface Treatment:Cadmiu Overall And Chromate OverallSurface Treatment:Cadmiu Overall And Chromate OverallSurface Treatment:Gap-416.ty 2.cl 3 Fed Spec Single Treatment Response Overall Or Mil-s-6049 Mil Spec Sth Material Response OverallSurface Treatment:Or-p-116.ty 2.cl 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Fastener Length:	0.890 Inches Minimum And 0.937 Inches Maximum
Grip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumInternal Drive Style:High-torqueNominal Thread Diameter:0.250 Inches0.438 Inches Nominal0.438 Inches NominalThread Quantity Per Inch:28Biomour Destination36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCourtersink Angle:99.0 Degrees Minimum And 01.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripRaterial Document And Cassification:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 OverallSurface Treatment:Cadmium Overall And Chromate Overall Or Steel Comp 4140 Chromate OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment:Unf	Head Style:	Flat Countersunk
Internal Drive Style:High-torqueNominal Thread Diameter:0.250 InchesGrip Length:0.438 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6059 Mil Spec 5th Material Response OverallSurface Treatment Document And Classification:Gap-416(ty 2, cl 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Head Diameter:	0.502 Inches Minimum And 0.507 Inches Maximum
Nominal Thread Diameter:0.250 InchesGrip Length:0.438 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6038 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmim Overall And Chromate OverallSurface Treatment Document And Classification:Or-s416,ty 2,cl 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Grip Length:0.438 Inches NominalGrip Length:0.438 Inches NominalThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6038 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallMarteria DocumentOry-416,ty 2,cl 3 Fed Spec Single Treatment Response OverallMateria DocumentOry-416,ty 2,cl 3 Fed Spec Single Treatment Response OverallMateria Response OverallMil Spec 4th Material Response OverallMateria Response OverallOverallMateria Response OverallMil Spec 4th Material Response OverallMateria Response OverallOverallMateria Response OverallMil Spec 6th Material Response OverallMateria Response OverallMil Spec 6th Material Response OverallMateria Response OverallMil Spec 6th Material Response OverallMateria Response OverallMil Spec 6th Ma	Internal Drive Style:	High-torque
Thread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:90.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mils-S626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6058 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:66.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Q-p-416,ty 2,cl 3 Fed Spec Single Treatment Response OverallUnfUnf	Grip Length:	0.438 Inches Nominal
Hardness Rating:36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum OverallCountersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8745 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallMaterial Series Designator:Unf	Thread Quantity Per Inch:	28
Countersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallQuep-416,ty 2,cl 3 Fed Spec Single Treatment Response OverallOverallMaterial Designator:Unf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate Overall Mulcassification:Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response OverallThread Series Designator:UnfUnf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6409 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Oq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response OverallUnfUnf	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mils-s5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallAut Classification:q-p-416,ty 2,cl 3 Fed Spec Single Treatment Response OverallMaterial Response OverallUnif	Surface Finish:	32.0 Microinches Grip
Material:Or Steel Comp 4130 OverallMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Or steel Comp 4130 OverallUnderstandUnderstand Spec Single Treatment Response OverallUnderstand Series Designator:Understand Spec Single Treatment Response Overall	Surface Finish:	32.0 Microinches Threads
Material Document And Classification:Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Material:	
Surface Treatment Document Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall And Classification: Unf	Material Document And Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758
And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas584 Professional/industrial Association Standard	Thread Series Designator:	Unf
	Specification/standard Data:	80205-nas584 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/close+tolerance+screws/NAS584-7</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.