

P/N NAS584-9

Description

Fastener Length: 0-63/64", Thread: 1/4-28, Thread Length: 1-1/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS5849

Minimum Qty (MOQ): 10 EA

NSN: 5305-00-802-4689

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



P/N NAS584-9 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.015 Inches Minimum And 1.062 Inches Maximum
Fastener Length:	0.015 Inches Minimum And 1.062 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.502 Inches Minimum And 0.507 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.562 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	2.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 4130 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas584 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS584-9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.