

P/N NAS585-14

Description

Fastener Length: 1-7/16", Thread: 1/4-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS58514

Minimum Qty (MOQ): 500 EA

NSN: 5305-00-551-6709

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS585-14 Specifications

Thread Direction: Right-hand Thread Length: 0.531 Inches Minimum Fastener Length: 1.390 Inches Minimum And 1.437 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.629 Inches Minimum And 0.633 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Internal Drive Style: High-torque Nominal Thread Dlameter: 0.312 Inches Grip Length: 0.3875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8130 Overall Or Steel Comp 4130 Overall Or Mils-s-6058 Mil Spec 2nd Material Response Overall Or Mils-s-6758 Mil Spec 6th Material Response Overall Or Mils-s-6049 Mil Spec 5th Material Response Overall Or Mils-s-6758 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Org-9-416.ty 2.cl 3 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf		
Tread Length: 0.531 Inches Minimum And 1.437 Inches Maximum Fastener Length: 1.390 Inches Minimum And 1.437 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.629 Inches Minimum And 0.633 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.312 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Material: 5teel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Material Document And Classification: Will-s-6026 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6758 Surface Treatment: Cadmium Overall And Chromate Overall And Classification: Unf	Thread Class:	3a
Fastener Length: 1.390 Inches Minimum And 1.437 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.629 Inches Minimum And 0.633 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.312 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5t	Thread Direction:	Right-hand
Head Style: Flat Countersunk Head Diameter: 0.629 Inches Minimum And 0.633 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.312 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4150 Overall Or Steel Comp 8735 Mil Spec 3rd Material Response Overall Or Mils-5626 Mil Spec 1st Material Response Overall Or Mils-5400 Mil Spec 2nd Material Response Overall Or Mils-6758 Material Document And Classification: Mils-5626 Mil Spec 1st Material Response Overall Or Mils-54040 Mil Spec 2nd Material Response Overall Or Mils-6758 Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qc-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Thread Length:	0.531 Inches Minimum
Head Diameter: 0.629 Inches Minimum And 0.633 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.312 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4130 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Mil-s-6098 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Fastener Length:	1.390 Inches Minimum And 1.437 Inches Maximum
Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Internal Drive Style: High-torque Nominal Thread Diameter: 0.312 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Ove	Head Style:	Flat Countersunk
Internal Drive Style: High-torque Nominal Thread Diameter: 0.312 Inches Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-60758 Mil Spec 6th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6098 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall And Classification: Unf	Head Diameter:	0.629 Inches Minimum And 0.633 Inches Maximum
Nominal Thread Diameter: Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp 4140 Overall Or Steel Comp 4140 Overall Or Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall O	Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Grip Length: 0.875 Inches Nominal Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unf	Internal Drive Style:	High-torque
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Material: Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Mil-s-6758 Surface Treatment Document And Classification: Thread Series Designator: Unf	Nominal Thread Diameter:	0.312 Inches
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unf	Grip Length:	0.875 Inches Nominal
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unf	Thread Quantity Per Inch:	24
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Grip 32.0 Microinches Threads Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Thread Series Designator: Unf	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Steel Comp 4130 Overall Or Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Surface Treatment Document And Classification: Thread Series Designator: Unf	Surface Finish:	32.0 Microinches Grip
Material: Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5400 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unf	Surface Finish:	32.0 Microinches Threads
Material Document And Classification:Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 6th Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response OverallThread Series Designator:Unf	Material:	
Surface Treatment Document And Classification: Thread Series Designator: Unf Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Unf	Material Document And Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6758
And Classification: Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Thread Series Designator: Unf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas585 Professional/industrial Association Standard	Thread Series Designator:	Unf
	Specification/standard Data:	80205-nas585 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS585-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS585-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS585-14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/NAS585-14 and selecting the quantity you want then click "add to cart".