

Description

Fastener Length: 7/16", Thread: 4-40, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS59007
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-183-3278
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS5900-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	0.438 Inches Nominal
Head Style:	Hexagon
Head Height:	0.049 Inches Minimum And 0.060 Inches Maximum
Width Between Flats:	0.181 Inches Minimum And 0.189 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Ams 6322 Assn Std 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas5900 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5900-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.