

Description

Fastener Length: 1-3/4", Thread: 6-32, Thread Length: 1-3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS590128 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-01-235-6438 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS5901-28 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.658 Inches Minimum And 1.750 Inches Maximum |
| Fastener Length: | 1.690 Inches Minimum And 1.750 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.080 Inches Minimum And 0.083 Inches Maximum |
| Width Between Flats: | 0.243 Inches Minimum And 0.251 Inches Maximum |
| Internal Drive Style: | Tri-wing Recess |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum |
| Screw Material: | Steel Comp E4340 Or Steel Comp 8740 |
| Screw Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas5901 Professional/industrial Association Standard |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5901-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.